

DATASOUND - LABORATORIES -

EMBEDDING THE FUTURE



Electronic Design



Panel PC / HMI



Single Board Computer



Industrial PC

Why choose DSL?

- Over 30 Years Industry Experience
- 5 Years Warranty on all Products
- Evaluation
 Products Available
- Lifetime Technical Support

Our Services

- Electronic Design
- Production Management
- Assembly and Test
- Bespoke BIOS Creation
- Industrial Embedded PC Solutions



www.dsl-ltd.co.uk



Call us on +44(0)1462 675530



Email us at sales@dsl-ltd.co.uk



Features /











- SUS 316 Stainless Steel
- Total IP66 Grade with M12 Waterproof Connector
- Wide range DC 9~36V Power Input
- Support Panel Mount & VESA Mount
- Support Projected Capacitive Touch
- Full Flat Bezel and Fanless Design
- Stainless Steel OSD Function Key
- ATEX/IECEx Zone2, Zone22 and C1D2/C2D2/C3 Certified





Specifications

| CI | TIC | atı | on | <u>s</u> / | 1 |
|----|-----|-----|----|------------|---|
| | | | | | |
| | | | | | |

1 x M12 8-pin for 2 x USB 2.0 for Touch Control with waterproof USB cover and chain Graph 1 x M12 12-pin for VGA with waterproof cover and chain 1 x M12 8-pin for OSD Cable & External OSD BOX with Function Keypad waterproof cover and chain 1 x M12 3-pin for DC power connector with waterproof cover and Power

21.5" TFT-LCD Display Type Max. Resolution 1920 x 1080 Max. Color 16.7M Luminance (cd/m²) View Angle 178(H) /178(V) Contrast 5000:1 Backlight Lifetime 50,000 hrs

Touch Screen

Projected Capacitive Touch Type Interface USB

Light Transmission(%) 90%

DC 9~36V Power Input Power Consumption AEx-121P: 24W

Construction 316 stainless steel chassis Mounting VESA mount 100 x 100, Panel mount (option)

IP Rating

Dimensions 571 x 362 x 75.1 mm

Net Weight 12.3 kg

Environmental

Certificate

Operating Temperature -20~60°C Storage Temperature -30~70°C

Humidity 10 to 95% @ 40°C, non-condensing

Safety CSA C22.2 No.61010

CE / FCC Class A


ATEx / IECEx Zone2 Ex ec ic IIC T4 Gc ATEx / IECEx Zone22 Ex tc IIIC T135°C Dc Class I, Division2, Group A,B,C,D,T4

Class II, Division2, Group F,G, T135°C

Class III

ANSI/ISA 12.12-01-2013 CSA Std., C22 No213-1987 Dimensions / /

Industrial Panel PC



Ordering Information

21.5" FHD IP66, 316 Stainless display, VGA input, external OSD box, Projected capacitive touch, 9~36V DC Power input, VESA Mount,

AEX-121P

Accessary: 1 x M12 for USB touch cable, 1 x VGA Cable, 1 x 3pin power

All specifications and photos are subject to change without notice.

input cable (w/o Adapter)

V 1.4