

Industrial Computing

Products and Services

Panel PC's



Industrial PC's




SBC's



Electronic Design



Industrial Displays



Embedding the future



Why Choose DSL?

- ✓ Lifetime technical support
- ✓ Fully customisable products
- ✓ Product branding (bezel colours + company logos)
- ✓ Free pre-installation of OS and your software



Our Services

- ✓ Electronic Design
- ✓ Production Management
- ✓ Assembly and test
- ✓ Bespoke BIOS creation



sales@dsl-ltd.co.uk

or call us on +44 (0)1462 675530



APC-3X18 Series

Core 2 Duo Fanless Panel PC



Features:

- ◆ Intel Socket P Processor, Support up to Intel P8600 2.4GHz Fanless.
- ◆ Flexible Expansion: PCI or PCIe X1
- ◆ Two User Accessible 2.5 SATA HDD, Support RAID 0, 1
- ◆ LED Backlight LCD Panel
- ◆ Aluminum Front Bezel
- ◆ IP 65 Front Panel
- ◆ 9~32V DC Wide Range Power Input



Aplex Taiwan Office (Headquarters)

15F-1, No.186, Jian Yi Road, Zhonghe Dist.,
New Taipei City, 235 Taiwan

TEL: +886-2-8226-2881 Fax: +886-2-8226-2883

E-mail: sales@aplex.com.tw
URL: www.aplex.com.tw

APC-3X18 Series

APC-3218/ 3518/ 3718/ 3918




• High Resolution Video Camera

Output Interface	USB 2.0
Image/Video Format	YUY2 & MJPG
Output size	VGA 640x480 (default) QQVGA 160x120 QVGA 320x240 SVGA 800x600 WXGA 1280x720 SXGA 1280x1024
Max. video frame	30fps @WXGA 1280x720 (MJPG)
Operating Current	145 mA ± 5%

• Front Side waterproof USB



• Front Side Keypad Control



Brightness
Up/Down

System on/off

Touch and Screen
on/off for cleaning



Accessible CF
card reader

Optional Stereo Speakers



• Optional Stereo Speakers

Input Power	2W 2.83V
Max Power	2.5W 3.16V
Output S.P.L.	83 ± 3 dB



Aplex Taiwan Office (Headquarters)

15F-1, No.186, Jian Yi Road, Zhonghe Dist.,
New Taipei City, 235 Taiwan
TEL: +886-2-8226-2881 Fax: +886-2-8226-2883

E-mail: sales@aplex.com.tw
URL: www.aplex.com.tw

APC-3X18 Series

APC-3218/ 3518/ 3718/ 3918

• Two easy accessible 2.5" SATA HDD Space



Two easy accessible 2.5" SATA HDD Space, support RAID 0 or 1 function, It offers low-risk data saving

• Optional DVD Combo




Optional DVD Combo Device for data backup Or media playback

PCI or PCIeX1 Expansion



• Rich I/O Ports



Aplex Taiwan Office (Headquarters)

15F-1, No.186, Jian Yi Road, Zhonghe Dist.,
New Taipei City, 235 Taiwan
TEL: +886-2-8226-2881 Fax: +886-2-8226-2883

E-mail: sales@aplex.com.tw
URL: www.aplex.com.tw

APC-3X18 Series

APC-3218/ 3518/ 3718/ 3918

Specifications

Model No.	APC-3218	APC-3518	APC-3718	APC-3918
System				
Processor	Intel Socket P processor support up to T9400 2.53GHz with system fan, Intel P8600 2.4GHz~T3100 1.9 GHz without fan			
System Memory	Two DDR3 SODIMM slot, up to 4GB each			
System Chipset	Intel GM45 + ICH9M-E			
External I/O Port	<ul style="list-style-type: none"> • 4 x USB 2.0 • 2 x GbE LAN • 1 x Audio Line-out/ MIC-in • 1 x VGA • 1 x HDMI • 2 x RS-232 (COM1 and COM2) • 1 x Terminal block for additional power switch • 2 x LED light • 1 x DB-9 option RS-422/485 (option) 			
Front Side I/O	1X USB 2.0 port with cap			
Storage	<ul style="list-style-type: none"> • 1 x CF slot External via SATA for option • 2 x 2.5" SATA HDD space, one HDD as standard, two HDDs as option for RAID 			
Front Side I/O	1 X USB 2.0 port with cap			
CD/DVD-R Device	Optional slim CD/DVD RW device via SATA (Not available if 2 HDDs and CF have been used)			
Wireless LAN+BT	Via mini-PCIe			
Web CAM	Option at front side by USB device			
Auto brightness	Auto Dimming as standard (option)			
Speaker	2 X 2W speaker (option)			
Expansion Slots	1 X PCI for option			
OS Support	Windows XP Professional, XP embedded, Windows embedded standard 7, Windows 7 Pro for embedded			
LCD				
Display Type	12" Color TFT	15" Color TFT	17" Color TFT	19" Color TFT
Max. Resolution	800x600	1024x768	1280x1024	1280x1024
Max. Color	262K	16.2M	16.2M	16.2M
Luminance (cd/m2)	350	400	350	450
View Angle	H:140° / V:110°	H:160° / V:140°	H:170° / V:160°	H:170° / V:160°
Backlight Lifetime	50,000 hrs			
Touch Screen				
Type	Resistive Type			
Light Transmission	80%			
Power Supply				
Power Input	DC 9~32V			
Mechanical				
Construction	Steel chassis			
IP Rating	Front Panel IP65			
Mounting	Panel / VESA 75x75 Mount			VESA 100x100 Mount
Dimension	390(W)x264(H)x91.5(D)mm	410(W)x310(H)x89.4(D)mm	439(W)x348(H)x97.3(D)mm	484(W)x400(H)x94.3(D)mm
Environmental				
Operating Temperature	-10~50 °C			
Storage Temperature	-20~60 °C			
Storage Humidity	10~90% @40 °C non-condensing			
	CE / FCC Class A			



Aplex Taiwan Office (Headquarters)

15F-1, No.186, Jian Yi Road, Zhonghe Dist.,
New Taipei City, 235 Taiwan
TEL: +886-2-8226-2881 Fax: +886-2-8226-2883

E-mail: sales@aplex.com.tw
URL: www.aplex.com.tw